

MCR-FL-C-UI-UI-B-DCI-24/230

Order No.: 2864325

The illustration shows a version of the product



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2864325>

Configurable 3-way isolating amplifier in bipolar version, standard signal range +/-20 mA or +/-10 V

Commercial data	
EAN	4017918976361
Pack	5 pcs.
Customs tariff	85437090
Weight/Piece	0.1055 KG
Catalog page information	Page 310 (IF-2007)

Product notes

WEEE/RoHS-compliant since:
09/12/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Input data	
Description of the input	Current input

Current input signal	0 mA ... 20 mA
	0 mA ... 10 mA
	4 mA ... 20 mA
	2 mA ... 10 mA
	-20 mA ... 20 mA
	-10 mA ... 10 mA
Max. input current	≤ 100 mA
Input resistance current input	Approx. 25 Ω
Description of the input	Voltage input
Voltage input signal	0 V ... 10 V
	0 V ... 5 V
	2 V ... 10 V
	1 V ... 5 V
	-10 V ... 10 V
	-5 V ... 5 V
Max. input voltage	≤ 30 V
Input resistance of voltage input	Approx. 1 MΩ
Output data	
Voltage output signal	0 V ... 10 V
	0 V ... 5 V
	2 V ... 10 V
	1 V ... 5 V
	-10 V ... 10 V
	-5 V ... 5 V
Current output signal	0 mA ... 20 mA
	0 mA ... 10 mA
	4 mA ... 20 mA
	2 mA ... 10 mA
	-20 mA ... 20 mA
	-10 mA ... 10 mA
Max. output voltage	15 V
Max. output current	35 mA
Load/output load voltage output	> 10 kΩ
Load/output load current output	≤ 600 Ω

Power supply

Range of supply voltages	24 V AC/DC ... 230 V AC/DC
Max. current consumption	60 mA (Without load current)
Power consumption	Approx. 2 VA (AC)
	Approx. 1 W (DC)

Connection data

Type of connection	Pluggable screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	14
Stripping length	8 mm
Screw thread	M3

General data

Width	12.5 mm
Height	99 mm
Depth	114.5 mm
Transmission error, max.	≤ 0.1 % (of end value)
Maximum temperature coefficient	0.01 %/K
Limit frequency (3 dB)	(8 kHz / 30 Hz switchable)
Frequency measuring range	48 Hz ... 62 Hz
Alignment zero	± 15 %
Alignment span	± 15 %
Step response (10-90%)	30 µs (At 8 kHz)
	15 ms (At 30 Hz)
Ambient temperature (operation)	-20 °C ... 65 °C
Degree of protection	IP20
Emitted interference	EN 61000-6-4
Immunity to interference	EN 61000-6-2:2005
Color	green
Housing material	Polyamide PA non-reinforced
Mounting position	Any
Conformity	CE compliant

Certificates / Approvals



Certification

CUL, UL

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2009 Phoenix Contact
Technical modifications reserved;