

PA-9312 / PA-9336 / PA9348: Power Amplifiers

For installations which require pure power, the Inter-M PA-9000 Series of power amplifiers are reliable, robust work horses. Units can be mains or DC powered so can easily operate in a critical system or in event/hire applications using battery power. Connections and controls are rear panel mounted to deter tampering or accidental adjustment.

Features:

- 120W/360W/480W Output power (100v/70v and 80Ω and 4Ω*)
- Audio/line in - (3 pin XLR)
- Audio/line out - (3 pin XLR)
- Input level control (on rear)
- Ground lift and HPF switches
- Fan cooled
- Thermal protection circuit
- DC power terminals
- 3U high, 19" rack mounting

* PA-9312 only has 4Ω low Z output. PA-9336 / PA-9348 have 4Ω and 8Ω options.

Specifications:

Model:	PA-9312:	PA-9336:	PA-9348:
Output Power	120W RMS @ 100v / 70v and 4Ω	360W RMS @ 100v / 70v and 8/4Ω	480W RMS @ 100v / 70v and 8/4Ω
Input Sensitivity/Impedance	1v / 10kΩ	1v / 10kΩ	1v / 10kΩ
Output Sensitivity/Impedance	1v / 10kΩ	1v / 10kΩ	1v / 10kΩ
Frequency Response	70Hz ~ 18KHz	70Hz ~ 18KHz	70Hz ~ 18KHz
Power Requirement	230v AC 50Hz / 24V DC	230v AC 50Hz / 24V DC	230v AC 50Hz / 24V DC
Dimensions	482(W) x 132(H) x 280(D)mm	482(W) x 132(H) x 280(D)mm	482(W) x 132(H) x 280(D)mm
Weight	14kg	21kg	22kg

