

Product datasheet

Specifications

switch I - 2 poles - 32 A



15010

⚠ Discontinued on: 15 July 2014

⚠ End-of-service on: 13 June 2018

⚠ Discontinued

Main

Product or component type	Switch
Device short name	I
Device application	Control
Poles description	2P
Utilisation category	AC-22A
Suitability for isolation	Yes

Complementary

[Ie] rated operational current	32 A at 415 V AC 50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to EN/IEC 60669-2-4
[Uimp] rated impulse withstand voltage	4 kV
control type	Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	2
Colour	Grey
Mechanical durability	300000 cycles
Electrical durability	30000 cycles
Connections - terminals	Tunnel type terminals - 1 x 1.5...1 x 10 mm ² - flexible Tunnel type terminals - 1 x 1.5...1 x 10 mm ² - rigid Tunnel type terminals - 2 x 2.5 mm ² - flexible Tunnel type terminals - 2 x 2.5 mm ² - rigid Tunnel type terminals - 2 x 4 mm ² - flexible Tunnel type terminals - 2 x 4 mm ² - rigid
Wire stripping length	9 mm
tightening torque	3.5 N.m

Environment

Standards	EN/IEC 60669-2-4
IP degree of protection	IP4

Pollution degree	2
------------------	---

Tropicalisation	2
-----------------	---

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	8 cm
------------------	------

Package 1 Width	1.8 cm
-----------------	--------

Package 1 Length	7.5 cm
------------------	--------

Package 1 Weight	66 g
------------------	------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins