

Product data sheet

Specifications



Hermetically sealed plug-in relays, SE Relays, 5A, 4 CO, 24VDC

782XDXH21-24D

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony Electromechanical Relays
Series name	782H series
Product or Component Type	Plug-in relay
Contacts type and composition	4 C/O
Relay Type	Hermetically sealed relay
Status LED	Without
[Uc] control circuit voltage	24 V DC
cover options	Hermetically sealed
[Ithe] conventional enclosed thermal current	5 A
Local signalling	Without LED without lockable test button

Complementary

class number	782H
Minimum switching current	500 mA 12 V AC 500 mA 12 V DC
Electrical durability	100000 cycles resistive IEC
Dielectric strength	1600 V AC between coil and contact 1600 V AC between poles
Control Type	Without lockable test button
Coil resistance	650 Ohm
Average coil consumption	0.90 W
Response Time	20 ms
Associated fuse rating	6 A gG at 400 V coordination type 2 for power circuit
Short-circuit current	1 kA
Average pole impedance	2 mOhm
Maximum switching voltage	240 V AC
[Ie] rated operational current	5 A at 120 V AC (on resistive load) 5 A at 240 V AC (on resistive load) 5 A at 30 V DC (on resistive load)
Mechanical durability	10000000 cycles
Contacts material	Silver alloy contacts
Shape of pin	Flat (faston type)
Width	0.90 in (22.75 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	1.3 in (32.5 mm)
Depth	1.13 in (28.75 mm)
Net Weight	1.6 oz (45 g)

Environment

Shock resistance	10 gn
Vibration resistance	6 gn 10...55 Hz)
Environmental characteristic	Hazardous location T5 70 °C
Product Certifications	UL CSA CE
Ambient Air Temperature for Storage	-76...185 °F (-60...85 °C)
Ambient Air Temperature for Operation	-49...158 °F (-45...70 °C)

Ordering and shipping details

Category	US10CP221127
Discount Schedule	0CP2
GTIN	3606480281082
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.132 in (2.875 cm)
Package 1 Width	0.896 in (2.275 cm)
Package 1 Length	1.132 in (2.875 cm)
Package weight(Lbs)	1.6 oz (45.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	1.2 in (3.0 cm)
Package 2 Width	4.3 in (11.0 cm)
Package 2 Length	5.1 in (13.0 cm)
Package 2 Weight	15.9 oz (450.0 g)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	7.09 in (18.0 cm)
Package 3 Width	10.2 in (25.8 cm)
Package 3 Length	13.2 in (33.5 cm)
Package 3 Weight	11.9 lb(US) (5.4 kg)

Contractual warranty



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 9

Environmental Disclosure [Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING:** This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair No

Use Again



Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

Technical Illustration

Dimensions




Image of product / Alternate images

Alternative





Image of product in real life situation

